Unit Specifications

TEAM HORNER	
N = M + M + M + M + M	
$ \land \lor \lor \lor \backsim \sim_{0} $	
Emplovee Owned	

G - 16.2

		SQ125	SQ145	SQ225	SQ120R	SQ166R
BTUs	80/80/80	101,000	121,000	143,000	110,000	126,000
(water temp/ambient air/	80/80/63	95,000	115,000	134,000	103,000	120,000
relative humidity)	80/50/63	62,000	75,000	90,000	72,000	82,000
С.О.Р.	80/80/80	6.5	7.1	6.5	5.5	5.6
Coefficient of Performance (water temp/ambient air/	80/80/63	6.1	6.8	6.1	5.3	5.3
relative humidity)	80/50/63	4.0	4.2	4.0	4.0	4.0
Refrigerant		R410A	R410A	R410A	R410A	R410A
Electrical	Heat or Heat & Cool	Н	Н	Н	H & C	H & C
	kW Input	4.6	5.1	6.4	5.9	6.6
A - 208-230/60/1	Voltage/Hz/Phase	А	A, B & G	A, B, E & G	A & B	A, B, E & G
B - 200-230/60/3 E - 380-415/60/3 G - 460/60/3	Max. Fuse Size	A - 60	A - 60 B - 50 G - 20	A - 60 B - 50 E - 30 G - 25	A - 60 B - 50	A - 60 B - 50 E - 30 G - 25
	Min. Circuit Ampacity	A - 40.5	A - 42.1 B - 31.0 G - 14.2	A - 42.1 B - 33.3 E - 18.4	A - 38.5 B - 31.0	A - 42.1 B - 33.3 E - 18.4

Over Temperature Alarm Kit available: part number STK0221 for single phase, STK0222 for three phase. Strongly recommended for all spa applications.

Water Flow	Min./Max. (gpm)	30/70	30/70	30/70	30/70	30/70
A Heater Bypass Kit is	required when flow rates exceed the n	naximum: part number	STK0135.			
Physical	Weight (lbs)	258	305	315	273	310
	Length x Width x Height (in)	34" x 34" x 44"	34" x 34" x 44"	34" x 34" x 44"	34" x 34" x 44"	34" x 34" x 44"
Shipping	Weight (lbs)	298	345	355	313	350
	Length x Width x Height (in)	37" x 36" x 51"	37" x 36" x 51"	37" x 36" x 51"	37" x 36" x 51"	37" x 36" x 51"

G - 16.2

Rated in accordance with AHRI standard 1160 water temp/ambient air/relative humidity Specifications subject to change



AquaCal AutoPilot, Inc. • 2737 24th Street North • St. Petersburg, FL 33713 • 727.823.5642



PoolSync **READY!**

HEATWAVE

Superior **EFFICIENCY** and **QUIETER** than any other heat pump on the market

HeatWave SuperQuiet[®]





MAXIMIZE THE ENJOYMENT OF YOUR SWIMMING POOL INVESTMENT

by heating your pool with an AquaCal® heat pump.

Free heat is taken from outside air and transferred to the pool water. A HEAT PUMP DOESN'T BURN ENERGY TO CREATE HEAT.

It only uses a small amount of energy to transfer FREE heat from the air to the pool.

The only heat pump that allows you to maximize the potential savings of a variable speed pump is an AguaCal[®]. Our patented ThermoLink[®] Titanium Heat Exchanger's unique flow characteristics allow you to run the pump at lower RPMs, ultimately saving you money.

This patented hydraulic design adds only 2 PSI at 45 gpm, increasing compatibility with two-speed & variable speed pumps.



Heat a pool for about 25% of the cost of heating it with gas



No other heat pump in its class is quieter

Heat pumps are green and have virtually no effect on your carbon footprint



AquaCal[®] has been producing quality heat pumps since 1981



Setting the standard for excellence in the industry for over 40 years

Over 375,000 happy customers worldwide

Smart Microprocessor Control with LCD Display

- Weather protected control with full text display provides easy-to-read menu options and unit status
- Ability to connect to external controllers for heating and cooling mode
- Hybrid functionality can initiate a gas heater when an extra boost of heat is needed

AquaTop

- Unique Air Flow Vectoring Top ensures optimal air flow for maximum efficiency
- World's ONLY integrated top that protects internal components and prevents debris like leaves and other vegetation from getting inside the heat pump, rotting and becoming corrosive
- Protection provided by the AquaTop allows for an extended 10 year warranty on the evaporator coil

Corrosion Proof Cabinet

- Louvered side panels protect evaporator coil while ensuring efficient air flow
- Rust and fade proof cabinet is impact resistant
- Built-in drain pan provides condensate management

ICEBREAKER® Heat & Cool Models

- Extends swimming season longer than any other heat pump on the market
- Continues to heat at freezing temperatures to minimize heat loss
- Cools your pool to a refreshing temperature

Now PoolSync[™] Ready P₃

• Adjust the mode to heat, cool or autotemp (when applicable), and set your temperature through the PoolSync app *Additional purchase of PoolSync WiFi Controller required

	NOTH		
POOLSY	INC IM		01
O FLOW	1.4P COLUMN		CN
1.947			
25 EQUIPM	ENT		
à caud	yno®		\rightarrow
g nut	ump		\rightarrow
P3	88	Ω	ŵ
r-26	uв	الي ا	









